

[54] **METHOD OF AND APPARATUS FOR MAKING DRIP-TYPE COFFEE**

[75] Inventor: **Richard Gregg**, Cincinnati, Ohio

[73] Assignee: **The Procter & Gamble Company**, Cincinnati, Ohio

[21] Appl. No.: **892,240**

[22] Filed: **Mar. 31, 1978**

Related U.S. Application Data

[62] Division of Ser. No. 726,073, Sep. 23, 1976.

[30] **Foreign Application Priority Data**

Sep. 22, 1977 [CA] Canada 287316

[51] Int. Cl.² **A47J 31/00**

[52] U.S. Cl. **99/283; 99/305**

[58] Field of Search 99/280, 281, 283, 282,
99/294, 295, 305, 307, 316

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,220,334 11/1965 Martin 99/282

3,408,921 11/1968 Freese 99/295
3,596,588 8/1971 Moss 99/282
4,064,795 12/1977 Ackerman 99/305

Primary Examiner—Robert W. Jenkins

Attorney, Agent, or Firm—Leonard Williamson; John V. Gorman; Rose A. Dabek

[57] **ABSTRACT**

A method and apparatus for making drip-type coffee beverage having improved flavor and aroma, and low bitterness characteristics. The method employs an extraction portion consisting essentially of warm 120° F.-75° F. water to infuse or extract roasted and ground coffee by the filter-drip method to issue a relatively strong filtered coffee extract into a container. A bypass-dilution portion of water, preferably 190° F. to 205° F., is added directly to the relatively strong filtered coffee extract to dilute the relatively strong filtered coffee extract to a predetermined beverage concentration at a preferred temperature. Also, a novel two-temperature split-water-stream coffeemaker for making coffee beverages by this method is provided.

10 Claims, 6 Drawing Figures

